



UNO ULTRA WHITE PLASTIC PAINT



PACKAGING

3L / 9L



DRYING TIME

2-3 Hours



CONSUMPTION

7-8 m²/l

Description

UNO ULTRA WHITE PLASTIC is a premium white plastic paint for interior use based on a high quality PVA-VEOVA synthetic resin. Suitable for painting sprayed surfaces, concrete, cement, marble plaster, plain cement, etc.

Surface Preparation

New surfaces made from marble plaster etc. must be primed with PN-301 PLASTIC PRIMER diluted 30% with water. For old surfaces it must be ensured that all surfaces are clean, free from dust and grease. Remove all poorly with abrasive paper No. 36 or No. 50 and prime the surface with PN-301 or PN-101 PLASTIC PRIMER.

Application

Do not apply to very cold or damp surfaces, in humid conditions and in temperatures below 5°C (41°F). Apply easily with brush or roller. Apply two coats of UNO ULTRA WHITE PLASTIC. For the first coat diluted 15%-20% with water and after 2-4 hours the second coat.

Coverage

UNO ULTRA WHITE PLASTIC covers 7-8m²/L according to the surfaces.

Drying Time

Dry in 1 hour in good drying conditions and it can be repainted in 2-3 hours later.

After Painting

Clean equipment immediately with water and soap.

Packaging

3L & 9L



TECHNICAL DATA

Appearance	White emulsion
Density (ISO2811, DIN 53217, ASTM D 1475)	1.55-1.59 g/cm ³
Viscosity (RVDV -2T,R7)	6000-9000 cp
Solids Content (Thermostat, 105°C/2Hours)	≤ 64 %
Intermolecular forces (RVDV -2T,R7)	85000-120000 newton/m ²
Kinematic viscosity (RVDV -2T,R7)	2500-6000 mm ² /s
pH	≥8
Particle Size (Elcometer 2050, ISO 1524; ASTM D 1210)	5-25 μm