



NEOSTUKO

Plaster Stucco



PACKAGING

15 kg



MIXING RATIO

4-5 L / 15kg



CONSUMPTION

1-2 kg/m²

Description

NEOSTUKO is a plaster stucco, composed with white cement, hydrated lime and special additives to improve adhesion and workability. NEOSTUKO creates a smooth surface without vertical slip. It is resistant and it can be used for indoor and outdoor surfaces.

Area of Use

- It is used to stucco walls and ceilings filled with mortar or prepared lime and cement-based mortar.
- It is used to stucco concrete surfaces.
- It is used to stucco gypsum-board walls and ceiling.

Application

- Mix NEOSTUKO with clean water slowly to obtain a homogeneous paste, free from lumps.
- After 10 minutes the product is ready for use.
- The material remains usable by mixing it periodically, without adding any water.
- The surface that the material will be applied should be sound, free from oil, grease and sufficiently dry.

Consumption

It consumes 1-2kg/m² depending on the surface.



TECHNICAL DATA (IN +23°C AND 50% U.R.)

Form	Powder
Colour	White
Storage	12 months when stored in the original sealed packaging in a dry place.
Mixing Ratio	4-5 litres of water/ 15kg powder
Application Temperature	(+5°C) - (+35°C)
Compressive Strength	≥ 10 N/mm ²
Bond Strength by Pull-Off	≥ 0.8 N/mm ²
Reaction to Fire	A1
Release of Dangerous Substances	See SDS