



AN-501 PINK ACRYLIC PRIMER



PACKAGING

0.75L / 3L / 9L



DRYING TIME

3-4 Hours



CONSUMPTION

12-15 m²/l

DESCRIPTION

AN-501 PINK is an acrylic primer with a "micronized resin" base, used for coating surfaces before painting them. It can be used for concrete, cement, plaster, gypsum, etc. It stabilizes the surface and decreases the porosity of the surface, thus reducing the paint consumption and avoiding cracking or falling of the paint. It also protects the surface from humidity by isolating it. AN-501 PINK dries quickly and creates the perfect surface for the final coating.

APPLICATION

The surface that will be painted must be dry (free from moisture) and free of dust, solid debris or oils. It is recommended that the damaged parts must be repaired before application. AN-501 PINK can be diluted with clean water in a 1:3 ratio. It can be applied with a brush or roller.

COVERAGE

It covers 12-15m²/l depending on the surface.

DRYING TIME

Touch dry in 2-4 hours in good dry conditions.

PACKAGE

0.75L, 3L and 9L



TECHNICAL DATA

Density	0.95-1.15 g/cm ³
pH	7
Viscosity	1050-2100mpa*s
Intermolecular Force	21000-42500 mpa
Drying Time	2-4 Hours