



## AN-801 BETON KONTAKT



PACKIGING

5KG / 20KG



DRYING TIME

24 Hours



CONSUMPTION

0.25 kg/m<sup>2</sup>

### Description

AN-801 BETON KONTAKT is an acrylic primer with a "micronized resin" base and supplemented with quartz, used for coating surfaces before painting them. It can be used for concrete, cement, plaster, gypsum, etc. It stabilizes the surface and decreases the porosity of the surface, thus reducing the final material consumption and avoiding cracking or falling of it. It also protects the surface from humidity by isolating it. AN-801 BETON KONTAKT dries quickly and creates the perfect surface for the final coating.

### Application

The surface that will be painted with AN-801 BETON KONTAKT must be dry (free from moisture) and free of dust, solid debris or oils. It is recommended that the damaged parts must be repaired before application. AN-801 BETON KONTAKT can be applied with a brush or roller.

### Coverage

AN-801 BETON KONTAKT covers 0.25kg/m<sup>2</sup> depending on the surface.

### Drying Time

Touch dry in 24 hours in good dry conditions.

### Package

5kg and 25kg.



## TECHNICAL DATA

Density	1.35-1.55 g/cm <sup>3</sup>
pH	8
Viscosity	12000-20000 mpa*s
Intermolecular Force	200000-430000 mpa
Drying Time	2 Hours

Name and Function / Emri dhe Pozicioni	<b>Klejdi GURI</b> Marketing Director / Drejtor i Marketingut	<b>Luan BASHA</b> R&D Manager / Menaxher i Kërkimit & Zhvillimit	<b>Marisa Koçi</b> Quality Management Systems Manager / Menaxhere e Sistemeve të Kontrollit të Cilësisë
Place and Date Of Issue / Vendi dhe Data e Lëshimit	Tirana / December 2022 Tiranë / Dhjetor 2022	Tirana / December 2022 Tiranë / Dhjetor 2022	Tirana / December 2022 Tiranë / Dhjetor 2022