



# ANTIRUST PROFESSIONAL



## PACKAGING

0.75L / 3.75 L



## DRYING TIME

2-4 Hours



## CONSUMPTION

10-12 m<sup>2</sup>/l

### DESCRIPTION

NEON ANTIRUST PROFFESIONAL suspension antirust is a professional high quality alkyd resin based paint, with coating of metal constructions destined to protect against rust and for decoration. Referring to its constituents, it has the property of inhibiting the process of oxidation (rust) of metal surfaces, environments internal and external.

### AREA OF USE

NEON ANTIRUST PROFFESIONAL used to paint metal surfaces in internal environments and external corrosion protection of these areas, as well as serving as a space filler that may have metal construction.

### COLOR

NEON ANTIRUST PROFFESIONAL paints are a great range of colors, which are listed in the catalog of the Company "NEON".

### USAGE

NEON ANTIRUST PROFFESIONAL is prepared by first diluting with diluent NC - 10:00 or NX - 20 000 or White Spirit "NEON" NW - 13:30 quantity 10% ÷ 20%, to obtain a consistency of paint which relatively easy to work with a paintbrush , roller or spray gun. Do not run on vertical surfaces.



## SKEDA TEKNIKE

Form	Liquid
Colour	See Catalog
Storage	12 months if stored in original sealed packaging in a dry place
Fineness	5 – 40 $\mu\text{m}$
Viscosity Deep Cup 4	200 – 300 sec
Density	0.94 – 1.35 g/ml
Coverage	10 – 12 m <sup>2</sup> /L
Drying Time	2 – 4 Hours
Dangerous Substances	See SDS