



ELITE PLASTIC PAINT



PACKAGING

3L / 9L / 15L



DRYING TIME

3-4 Hours



CONSUMPTION

9-11 m²/l

DESCRIPTION

ELITE PLASTIC is an ecological matt emulsion paint for interior use. Suitable for painting plastered surfaces, concrete, cement, marble plaster, plain cement etc.

SURFACE PREPARATION

New surfaces made from marble plaster etc, must be primed with PN-301 primer diluted 15-20% with water or PN-101. For old surfaces it must be ensured that they are clean, free from dust and grease.

APPLICATION

Do not apply on humid conditions and in temperatures below 5°C (41°F). Apply easily with brush or roller. Apply two coats ELITE PLASTIC. Dilute the first coat with 15-20% water and after 2 – 4 hours apply the second coat.

COVERAGE

ELITE PLASTIC cover 9- 11 m²/L depending on the surface.

PACKAGE

3L, 9L and 15L.



TECHNICAL DATA (IN +23°C AND 50% U.R.)

Appearance	White water emulsion
Density (ISO2811, DIN 53217, ASTM D 1475)	1.56-1.60 g/cm ³
Viscosity (RVDV -2T,R7)	3500-7500 cp
Solids Content (Termostat, 105°C/2orë)	≤ 65 %
Intermolecular forces (RVDV -2T,R7)	60000-140000 newton/m ²
Kinematic viscosity (RVDV -2T,R7)	2100-4500 mm ² /s
pH	≥8
Particle Size (Elcometer 2050, ISO 1524; ASTM D 1210)	10-30 μm