



ELITE WALL PAINT



PACKAGING

3L / 9L / 15L



DRYING TIME

3-4 Hours



CONSUMPTION

6-7 m²/l

Description

ELITE WALL PAINT is an ecological emulsion paint that is suitable for interior use. ELITE WALL PAINT can be used for ceilings, walls, etc.

Application

The substrate should be clean, free of dust, oil, or grease. Before applying ELITE WALL PAINT to surfaces they should first be primed with the plastic primer PN-101 or PN-301 1-2 layers, depending on the absorbency of the substrate. Do not apply to cold and damp surfaces, in humid conditions or in temperatures below 5 (41). Apply easily with a brush or roller. Dilute ELITE WALL PAINT with 15% water before use.

Coverage

ELITE WALL PAINT consumes 6-7m²/L depending on the surface.

Storage

12 months from production date if stored in original, unopened packaging, in places protected from moisture and frost.



TECHNICAL DATA (IN +23°C AND 50% U.R.)

Appearance	White water emulsion
Density (ISO2811, DIN 53217, ASTM D 1475)	1.58-1.63 g/cm ³
Viscosity (RVDV -2T,R7)	4000-6500 cp
Solids Content (Termostat, 105°C/2orë)	≤ 70 %
Intermolecular forces (RVDV -2T,R7)	60000-120000 newton/m ²
Kinematic viscosity (RVDV -2T,R7)	2400-4000 mm ² /s
pH	≥8
Particle Size (Elcometer 2050, ISO 1524; ASTM D 1210)	10-30 μm