



GLORIA BETAPLAST PLASTIC PAINT



PACKAGING

3L / 9L / 15L



DRY TIME

3-4 Hours



CONSUMPTION

9-11 m²/l

Description

GLORIA BETAPLAST is a vinyl matt emulsion paint for interior use, based on copolymer resin of high quality PVA - VEOVA. Suitable for painting spatulated surfaces, concrete cement, marble plaster, plain cement etc.

Surface Preparation

New surfaces made from marble plaster etc, must be primed with PN-301 primer diluted 15-20% with water or PN-101. For old surfaces it must be ensured that they are clean, free from dust and grease. Remove all poorly with abrasive paper No. 36 or No. 50 and prime the surface with PN-301 or PN-101 primer.

Application

Do not apply on very cold or damp surfaces, in humid conditions and in temperatures below 5°C (41°F). Apply easily with brush or roller. Apply two coats GLORIA BETAPLAST. Dilute the first coat with 15-20% water and after 2 – 4 hours apply the second coat.

Coverage

GLORIA BETAPLAST cover 9- 11 m²/L according to the surfaces.

Drying Time

Touch dry in 1 hour in good drying conditions and it is repainted in 2 - 3 hours later.

After Painting

Clean equipment immediately with water and soap.

Package

3 L, 9 L and 15 L.



TECHNICAL DATA

Appearance	White emulsion
Density (ISO2811, DIN 53217, ASTM D 1475)	1.56-1.60 g/cm ³
Viscosity (RVDV -2T,R7)	3500-5500 cp
Solids Content (Thermostat, 105°C/2orë)	≤ 65 %
Intermolecular forces (RVDV -2T,R7)	60000-120000 newton/m ²
Kinematic viscosity (RVDV -2T,R7)	2100-3500 mm ² /s
pH	≥8
Particle Size (Elcometer 2050, ISO 1524; ASTM D 1210)	10-40 μm