



NEOFAS GRAFIATO FULL



PACKAGING

25kg



DRYING TIME

24 Hours



CONSUMPTION

1mm = 2kg/m²
1.5mm = 3kg/m²
2mm = 3.6kg/m²

DESCRIPTION

NEOFAS GRAFIATO FULL is a topcoat plaster, ready for use, based on acrylic binders. It has an elastic structure as well as durability for facades over the thermal insulation system and the bottom plaster. It has a high resistance to atmospheric conditions. NEOFAS GRAFIATO FULL offers exceptional processing quality.

SURFACE PREPARATION

Surfaces must be clean from dust and grease. It is recommended to paint first the surface with primer NEOPRIM.

APPLICATION

Do not apply to very cold or damp surface, in damp humid condition and in temperature under 5°C (41°F).

CONSUMPTION

Depending on its severity. For 1mm it consumes approximately 2kg/m², 1.5mm about 2kg/m² and 2mm about 3.6 kg/m².

DRYING TIME

In good drying conditions, the partial dry after 24 hours and final dry after 14 days.

PACKAGE

25kg



TECHNICAL DATA (IN +23°C AND 50% U.R.)

Form	Paste
Color	White
Storage	12 muaj nëse ruhet në paketimin original të mbyllur, në një vend të thatë.
Density (EN ISO 2811, DIN 53217, ASTM D 1475)	1.7-2.0 g/cm ³
Viscosity (RVDV -2T, R7)	15000-30000 cp
pH	≥8
Resistance against humidity	Dry after 24 hours in normal conditions
Application Temperature	(+5°C) - (+35°C)
Shear Stress (RVDV -2T, R7)	30000-600000 newton/m ²
% (RVDV -2T, R7)	10-90%
Kinematic Viscosity (RVDV -2T, R7)	5000-10000 mm ² /s

CONSUMPTION

1mm	2kg/m ²
1.5mm	3kg/m ²
2mm	3.6kg/m ²