



# NEOPRIM PRIMER FOR GRAFIATO



#### PACKAGING

5kg / 25kg



#### DRYING TIME

24 Hours



#### CONSUMPTION

0.2-0.25kg/m<sup>2</sup>

### Product Description

NEOPRIM is a white pigment primer, suitable for undercoating paintings of a surface, prior to the application with NEOFAS GRAFIATO. It can also be used for other types of plasters. Its production is based on acrylic binders and mineral fillers.

### Use

NEOPRIM Primer gives to the surface the same level of absorption. It has a big penetration and resistance. After the application of NEOPRIM, the water absorption on the surface will be much lower.

### Application

Do not apply to very cold or damp surface, in dump humid condition and in temperature under 5°C(41°F).

It is ready to use or can be diluted with just a little water. Apply with roller or shovel.

### Consumption

Depending on the surface and from the film thickness 0.2 – 0.25kg/m<sup>2</sup>.

### Tools

Clean the equipment with water, immediately after the job.

### Package

5kg and 20kg.



## TECHNICAL DATA (IN +23°C AND 50% U.R.)

Form	Paste
Color	White
Storage	12 months when stored in the original sealed packaging in a dry place.
Density (EN ISO 2811, DIN 53217, ASTM D 1475)	1.65-1.75 g/cm <sup>3</sup>
Viscosity (RVDV -2T, R7)	5500-6500 cp
pH	≥8
Resistance against humidity	Dry after 24 hours in normal conditions
Application Temperature	(+5°C) - (+35°C)
Shear Stress (RVDV -2T, R7)	10000-15000 newton/m <sup>2</sup>
% (RVDV -2T, R7)	10-70%
Kinematic Viscosity (RVDV -2T, R7)	2000-5000 mm <sup>2</sup> /s