



NEOLAC WOOD



PACKAGING

0.75L / 3.75 L



DRY TIME

1-2 Hours



CONSUMPTION

10-12 m²/l

PRODUCT DESCRIPTION

NEOLAC STONE is transparent acrylic stone varnish, suitable for interior and exterior use. It penetrates the surface without creating a film and consequently without yellowing or lifting. It enhances the natural colour of the surface and protects the stone from humidity and stain absorption. Enhances the natural beauty of the stone.

APPLICATION

Surfaces should be clean, dry, free from grease, dust or old varnishes. Stir well before use. Apply one or two coats with a roller, brush or airless spray gun without dilution. Do not apply at temperatures below 5°C and above 35°C and/or relative humidity above 80%. The product must be kept closed in a cool, dry, well ventilated area protected from direct sunlight.

COVERAGE

10-12m²/l according to the surface absorption.

DRYING TIME

Touch dry after 1-2 hours and can be recoated after 3-4 hours. Drying time depends on weather conditions.

PACKAGE

0.75L and 3.75L



TECHNICAL DATA

Density: (EN ISO 2811- 1)	0.92 ± 0.02 kg/l
Viscosity (mPa.s): (EN ISO 2884- 2)	560 (23°C)
Capillary water absorption: (EN ISO 1062- 3: W3 Low, w ≤ 0,1)	0.02 kg/m ² /h0.5
Adhesion: (EN ISO 4624)	2 N/mm ²
Drying time: (EN ISO 9117)	1-2 h (touch dry)
Recoat time: (EN ISO 9117)	3-4 h
Dangerous Substances	Check SDS