



NEOLAC WOOD



PACKAGING

0.75L / 3.75 L



DRY TIME

4-6 Hours



CONSUMPTION

7-8 m²/l

PRODUCT DESCRIPTION

NEOLAC WOOD is a top-quality decorative varnish based on alkyd resins for internal and external use.

USE

On properly prepared surfaces of wood.

APPLICATION

Easy to apply by brush, roller or spray. It gives a shining area and excellent resistance to weathering agents. It can penetrate inside of wood surfaces, protected from bacteria and insects. Before used, the surface must be clean from dusts. Do not apply at temperatures below 5°C and above 35°C and/or relative humidity above 80%.

THINNERS

Diluted with White Spirit NEON NW-13.00 and solvent NEON NX-20.00 or NC-10.00 at about 10%-20% on varnish.

COVERAGE

7-8m²/l over a normal, smooth surface.

DRYING TIME

4-6 hours under normal weather conditions.

PACKAGE

0.75L and 3.75L



TECHNICAL DATA

Density: (EN ISO 2811- 1)	0.92 ± 0.02 kg/l
Viscosity (mPa.s): (EN ISO 2884- 2)	560 (23°C)
Capillary water absorption: (EN ISO 1062- 3: W3 Low, w ≤ 0,1)	0.02 kg/m ² /h0.5
Adhesion: (EN ISO 4624)	2 N/mm ²
Drying time: (EN ISO 9117)	7 h (touch dry)
Recoat time: (EN ISO 9117)	24 h
Dangerous Substances	Check SDS