



NEOLAC NEOPROTECT



PACKAGING

0.75L / 3.75 L



DRYING TIME

12 Hours



CONSUMPTION

12-15 m²/l

PRODUCT DESCRIPTION

NEOLAC NEOPROTECT is an impregnation preservative and colour varnish that protects wood against woodworms and decay. It prevents mold growth that may cause wood discoloration. It does not create a surface film; therefore, it will not crack or peel off. It is designed to allow wood to breathe and be repainted without further previous treatments.

USAGE

It is suitable for interior and exterior woodwork, treated or untreated, fences, beams, windows, shelters and gardening furniture.

APPLICATION

Ready to use. Stir well before using. Brush evenly in the direction of the wood grain. For outdoors apply 2 coats at 12-hour intervals. It can be applied by spray or roll. Do not apply at temperatures below 5°C and above 35°C and/or relative humidity above 80%.

NOTE: Applying multiple coats will produce a darker colour.

COVERAGE

12-15m²/l according to the wood surface absorption.

DRYING TIME

Touch dry after 1 hour, completely dry in 12 hours when under normal weather conditions.

PACKAGE

0.75L, 3.75L and 16L.



TECHNICAL DATA

Density (EN ISO 2811- 1)	0.79-0.83 kg/l
Viscosity (EN ISO 2884- 2)	15 (23°C)
Drying Time (EN ISO 9117)	12 h
Recoat Time (EN ISO 9117)	24 h
Dangerous Substances	Check SDS