



ORALAC PROFESSIONAL



PACKAGING

0.75L / 3.75 L



DRYING TIME

4-6 Hours



CONSUMPTION

14-16 m²/l

PRODUCT DESCRIPTION

ORALAC is an alkyd based, top-quality paint finish for exterior and interior use. ORALAC is used on properly prepared metallic, wooden or wall surfaces.

APPLICATION

ORALAC is prepared by first diluting it with White Spirit NEON NW-13.00 and the solvent NEON NX-20.00 or NC-10.00 at about 10% ÷ 20% on paint. Easily applicable with brush, roller or spray gun. It is resistant to atmospheric conditions and it provides a super colour retention. It has an excellent spread, and it does not run-on vertical surfaces.

COVERAGE

It covers 14-16m²/l over a normal smooth undercoated surface by anticorrosive NEON ANTIRUST or ANTICOR.

DRYING TIME

4-6 hours under normal weather conditions.

PACKAGE

0.75L and 3.75L



TECHNICAL DATA

Colour	See Catalog
Density (ISO2811, DIN 53217, ASTM D 1475)	0.90- 1.35 g/cm ³
Fineness (Elcometer 2050, ISO 1524; ASTM D 1210)	5-40 µm
Coverage	14- 16 m ² /L
Drying Time(ASTM D-5895)	4-6 Hours
Storage conditions	Protect from frost