



RS 35 ROAD PAINT



PACKAGING

0.75L/3.75L



DRYING TIME

15-60 Min



CONSUMPTION

1-1.4 m²/l

Description

RS ROAD PAINT is a paint based on acrylic resins and solvents used to mark roads. It dries very quickly, within 60 minutes it can be stepped on the painted surface. It has great adhesion, friction and durability. RS ROAD PAINT maintains its shine even after application in all weather conditions. In its composition there are glass beads that make this product reflex. In addition, its mixture with special sand increases friction and avoids slipping. Available in the following colors: white, yellow and optional.

Field Of Application

RS ROAD PAINT is used to mark asphalt roads, concrete roads, speed bumps and mostly to marked on sidewalks, as well as in other areas with traffic.

Preparation

The surface to be painted must be cleaned of debris, dust, grease or previous layers of paint that are poorly connected to the surfaces (swelled layers). The surface must be dry and clean.

Usage

RS ROAD PAINT is mixed with solvent up to 10% as needed. It should be mixed well. With the obtained mass, we paint the surface that we want to paint. Depending on the conditions, painting can be done with a gun, roller or brush.

Packing

0.75L and 3.75L.



TECHNICAL DATA

Color	White, Yellow, Burgundy, Transparent or Pigmented
Density (ISO2811, DIN 53217, ASTM D 1475)	1.5-1.6 g/cm ³
The fineness of the particle (Elcometer 2050, ISO 1524; ASTM D 1210)	40-80 µm
Coverage	1-1.4 m ² /L
Drying Time (ASTM D-5895)	15-60 Min
Dry Content (ISO 3251-03)	37 % (±2)