



UNO PLASTIC PAINT



PACKAGING

3L / 9L / 15L



DRY TIME

3-4 Hours



CONSUMPTION

14-16 m²/l

Description

UNO PLASTIC is a premium vinyl matt emulsion paint for interior use based on copolymer resin of high quality PVA-VEOVA. Suitable for painting spatulated surfaces, concrete, cement, marble plaster, plain cement etc. After 15-20 days can be washed with moderate detergent solutions rinse with clean water and allow dry without causing any paint removal.

Surface Preparation

New surfaces made from marble plaster etc. must be primed with PN-301 PLASTIC PRIMER diluted 30% with water. For old surfaces it must be ensured that all surfaces are clean, free from dust and grease. Remove all poorly with abrasive paper No. 36 or No. 50 and prime the surface with PN-301 or PN-101 PLASTIC PRIMER.

Application

Do not apply to very cold or damp surfaces, in humid conditions and in temperatures below 5°C (41°F). Apply easily with brush or roller. Apply two coats of UNO PLASTIC. For the first coat diluted 15%-20% with water and after 2-4 hours the second coat.

Coverage

UNO PLASTIC covers 14-16m²/L according to the surfaces.

Drying Time

Dry in 1 hour in good drying conditions and it can be repainted in 2-3 hours later.

After Painting

Clean equipment immediately with water and soap.

Package

3L, 9L and 15L.



TECHNICAL DATA

| | |
|----------------------------------------------------------|------------------------------------|
| Appearance | White emulsion |
| Density (ISO2811, DIN 53217, ASTM D 1475) | 1.55-1.59 g/cm ³ |
| Viscosity (RVDV -2T,R7) | 6000-9000 cp |
| Solids Content (Thermostat, 105°C/2Hours) | ≤ 64 % |
| Intermolecular forces (RVDV -2T,R7) | 85000-120000 newton/m ² |
| Kinematic viscosity (RVDV -2T,R7) | 2500-6000 mm ² /s |
| pH | ≥8 |
| Particle Size (Elcometer 2050, ISO 1524; ASTM D 1210) | 5-25 μm |