



# UNO WALL PAINT



#### PACKAGING

3L / 9L / 15L



#### DRYING TIME

3-4 Hours



#### CONSUMPTION

10-12 m<sup>2</sup>/l

### Description

UNO WALL PAINT is a vinyl matt emulsion paint for interior use based on copolymer resin of high quality PVA-VEOVA. Suitable for painting spatulated surfaces, concrete, cement, marble plaster, plain cement etc.

### Surface Preparation

New surfaces made from marble plaster etc. must be primed with PN-301 primer diluted 30% with water. For old surfaces must ensure that all surfaces are clean free from dust and grease. Remove all poorly adhesion with abrasive paper NO 36 or NO 50 and prime the surface with PN-301 or PN-101 primer.

### Application

Do not apply on very cold or damp surfaces, in humid conditions and in temperatures below 5°C (41°F). Apply easily with brush or roller. Apply two coats UNO WALL PAINT. Dilute the first coat with 10-15% water and after 2-4 hours apply the second coat.

### Coverage

UNO WALL PAINT covers 5-6m<sup>2</sup>/L depending on the surface.

#### Drying Time

Touch dry in 1 hour in good drying conditions and it is repainted in 2-3 hours later.

### After Painting

Clean equipment immediately with water and soap.

### Package

3L, 9L and 15L.



## TECHNICAL DATA (IN +23°C AND 50% U.R.)

Appearance	White emulsion
Density(ISO2811, DIN 53217, ASTM D 1475)	1.55-1.57 g/cm <sup>3</sup>
Viscosity(RVDV -2T,R7)	4000-6700 cp
Solids Content (Termostat, 105°C/2orë)	≤ 64 %
Intermolecular forces (RVDV -2T,R7)	85000-120000 newton/m <sup>2</sup>
Kinematic viscosity(RVDV -2T,R7)	2500-4300 mm <sup>2</sup> /s
pH	≥8
Particle Size (Elcometer 2050, ISO 1524; ASTM D 1210)	5-25 µm