



ZMALTOLAC NORMAL



PACKAGING

0.75L / 3.75 L



DRYING TIME

4-6 Hours



CONSUMPTION

7-8 m²/l

PRODUCT DESCRIPTION

ZMALTOLAC is a top-quality finish paint for interior and exterior use. ZMALTOLAC is used for painting metallic, wooden and wall surfaces.

APPLICATION

ZMALTOLAC is prepared by first diluting it with White Spirit NEON NW-13.00 and the solvent NEON NX-20.00 or NC-10.00 at about 10% ÷ 20% on paint. Easily applicable with brush, roller or spray gun. It is resistant to atmospheric conditions and it provides a shining surface.

COVERAGE

It covers 7-8m²/l over a normal smooth under-coated surface by anticorrosive NEON ANTIRUST or ANTICOR.

DRYING TIME

4-6 hours under normal weather conditions.

PACKAGE

0.75L and 3.75L



TECHNICAL DATA

Form	Liquid
Colour	See Catalog
Storage	12 months if stored in original sealed packaging in a dry place
Fineness	5 – 40 μm
Viscosity Deep Cup 4	200 – 300 sec
Density	0.94 – 1.35 g/ml
Coverage	7-8 m ² /L
Drying Time	4 – 6 Hours
Dangerous Substances	Shiko SDS