



# AN-401 ACRYLIC PRIMER



#### PACKAGING

0.75L / 3L / 9L



#### DRYING TIME

2-4 Hours



#### CONSUMPTION

12-20 m<sup>2</sup>/l

### DESCRIPTION

Primer for interior walls and floors prior to the application of levelling compounds and adhesive mortars on absorbent or non-absorbent substrates.

### FIELD OF APPLICATION

Application examples

- Preparation of concrete screeds or slabs.
- Preparation of wood surfaces, wood panels (CTB-H, CTB-X), old tiles or natural stone.
- Preparation of thermoplastic slabs
- Preparation of surfaces on which traces of glue or old, well-adhering levelling compounds remain.

### CHARACTERISTICS

AN-401 is a primer based on acrylic resins in water dispersion.

Product properties:

- Ready to use
- Easy roller application
- Fast drying
- Solvent-free

### APPLICATION

Apply AN-401 in one continuous coat by brush or roller and allow to dry.

Once the primer is completely dry, you can apply levelling compound or adhesive. Drying times vary according to substrate absorption and ambient conditions (temperature and humidity). However, we recommend waiting no longer than 24 hours.



---

## TECHNICAL DATA

---

Density	0.95-1.15 g/cm <sup>3</sup>
pH	7
Viscosity	1300-2000 mpa*s
Intermolecular Force	27800-42500 mpa
Drying Time	2-4 Hours