

AN-401 ACRYLIC PRIMER

Good penetrating, multi-purpose acrylic water based primer.



PACKAGING
0.75L/3L/9L



DRYING TIME
2-4 Hours



CONSUMPTION
10-12 m²/L

Description

AN-401 ACRYLIC PRIMER is a polymer emulsion with good penetrating ability used to consolidate porous substrates, ensuring proper adhesion of water based paints, tile adhesives and liquid-applied elastomeric membranes.

Area of Use

- It is used to ensure the adhesion of water-based paints to substrates made of concrete, masonry, façade render and gypsum boards.
- It is used to ensure the adhesion of tile adhesives and liquid-applied elastomeric membranes to porous substrates.

Substrate Preparation

The surface to be primed must be dry and free of dust, grease, dirt, etc.

Application

AN-401 ACRYLIC PRIMER is stirred and applied over the substrate by brush, roller, or spray.

Consumption

It covers 10-12m²/L depending on the surface.

Features





Technical Data (IN +23° C AND 50% U.R.)

Density	0.95-1.15 g/cm ³
pH	7
Viscosity	1300-2000 mpa*s
Intermolecular Force	27800-42500 mpa
Drying Time	2-4 Hours

NEON Paints

Tiranë, Albania

info@neonpaints.eu

www.neonpaints.eu

T: +355 69 20 94 570

THIS TECHNICAL DATA SHEET SUPERSEDES ALL PREVIOUS EDITIONS RELEVANT TO THIS PRODUCT

2/2

DISCLAIMER: The above technical data, information, recommendations and guidance are based on scientific and technical knowledge, laboratory studies and long experience. However, the above information is considered to be as indicative and should be reviewed in any case in relation to each specific application conditions. Consequently, the suitability of each product in any application must be evaluated after referring to the updated Technical Data Sheet and to the website www.matis-eu.com, as well as after contacting the technical support department, in case of necessity. Our company guarantees the quality of the product itself, whilst in any case the user/applicant is exclusively responsible for any undesirable failures after using the product.