

AN-501 ACRYLIC PRIMER

Acrylic, micronized, water-based primer with high adhesion strength and high penetration properties that stabilizes the surface and decreases the porosity of the surface.



PACKAGING
0.75L/3L/9L



DRYING TIME
2-4 Hours



CONSUMPTION
12-15 m²/L

Description

AN-501 ACRYLIC PRIMER is an acrylic, micronized, water-based primer with high adhesion strength and high penetration properties that stabilizes the surface and decreases the porosity of the surface.

Area of Use

- It is used to ensure the adhesion of water-based paints to substrates made of concrete, masonry, façade render and gypsum boards.
- It is used to ensure the adhesion of tile adhesives and liquid-applied elastomeric membranes to porous substrates.

Substrate Preparation

The surface to be primed must be dry and free of dust, grease, dirt, etc.

Application

AN-501 ACRYLIC PRIMER is stirred and applied over the substrate by brush, roller, or spray.

Consumption

It covers 12-15m²/L depending on the surface.

Features





Technical Data (IN +23° C AND 50% U.R.)

Density	0.95-1.15 g/cm ³
pH	7
Viscosity	1050-2100mpa*s
Intermolecular Force	21000-42500 mpa
Drying Time	2-4 Hours

NEON Paints

Tiranë, Albania

info@neonpaints.eu

www.neonpaints.eu

T: +355 69 20 94 570