

HYDRO CLASSIC WALL PAINT

Professional distemper paint formulated to offer breathability for the walls and ceilings with good coverage.



PACKAGING
3L/9L



DRYING TIME
2-3 Hours



CONSUMPTION
5-6 m²/L

Description

HYDRO CLASSIC WALL PAINT is a professional distemper paint formulated to offer breathability for the walls and ceilings with good coverage.

Area of Use

-It is used for indoor applications, on new or old surfaces, on all common building materials, such as concrete, plaster, gypsum boards, etc.

Substrate Preparation

The surface must be dry and free of dust, grease, dirt, etc. For surface smoothing, NEOSTUKO should be used. The surface must be primed with PN-101 PLASTIC PRIMER or PN-301 PLASTIC PRIMER to stabilize and increase the adhesion of the paint to the surface.

Application

HYDRO CLASSIC WALL PAINT should be thoroughly stirred before use. It is applied as is or thinned with clean water, in two coats using a roller, brush, or airless gun. The second coat is applied once the first one has completely dried.

Consumption

HYDRO CLASSIC WALL PAINT covers 5-6 m²/L depending on the surface.

Features



Technical Data (IN +23° C AND 50% U.R.)

Appearance	White emulsion
Density (ISO2811, DIN 53217, ASTM D 1475)	1.58-1.62 g/cm ³
Viscosity (RVDV -2T,R7)	4000-6500 cp
Intermolecular forces (RVDV -2T,R7)	60000-120000 newton/m ²
Kinematic viscosity (RVDV -2T,R7)	2400-4000 mm ² /s
pH	≥8
Particle Size	10-30 μm

NEON Paints

Tiranë, Albania

info@neonpaints.eu

www.neonpaints.eu

T: +355 69 20 94 570