

NEOFAS SILICONE FULL

Premium, silicone, ready-to-use, exceptionally water-repellent and vapour permeable facade render.



PACKAGING
25kg



CONSUMPTION
2kg/m²-1mm | 3kg/m²-1.5mm | 3.6kg/m²-2mm

Description

NEOFAS SILICONE FULL is a premium, silicone, ready-to-use, exceptionally water-repellent and vapour permeable facade render. It offers high elasticity and high adhesion to the substrate. NEOFAS SILICONE FULL has excellent vapour permeability, crack prevention and there is no need to paint the façade after application.

Area of Use

-It is used as a thin finishing coat of render works to create a white or coloured, water-repellent finish.

-It is used as a decorative finish in the NEON Paints Thermal Insulation Systems.

Substrate Preparation

The surface should be free of dust, grease, loose particles, paints, etc. It is recommended to dampen it before application. Use NEOPRIM PRIMER GRAFIATO to increase the adhesion of NEOFAS SILICONE FULL to the surface.

Application

NEOFAS SILICONE FULL should be thoroughly stirred before application, in slow, circular motions to prevent air entrapment. NEOFAS SILICONE FULL is applied by hand, using a smooth, stainless steel trowel, or with a plastering machine.

While still not dried complexly (5-15 min. after its application), NEOFAS SILICONE FULL is treated (pressed) with a plastic trowel.

Consumption

It consumes 2kg/m² for 1mm, 3kg/m² for 1.5mm and 3.6kg/m² for 2mm depending on the surface.

Features



NEON
COLORING
SYSTEM

BASES
TR

Technical Data (IN +23° C AND 50% U.R.)

| | |
|---|------------------------------------|
| Appearance | Paste |
| Colour | White |
| Density (ISO2811, DIN 53217, ASTM D 1475) | 1.7-2 g/cm ³ |
| Viscosity (RVDV -2T,R7) | 15000-30000 cp |
| Shear Stress (RVDV -2T,R7) | 30000-600000 newton/m ² |
| Kinematic viscosity (RVDV -2T,R7) | 5000-10000 mm ² /s |
| pH | ≥8 |

NEON Paints

Tiranë, Albania

info@neonpaints.eu

www.neonpaints.eu

T: +355 69 20 94 570