

NEOPRIM PRIMER GRAFIATO

Water-based, white, acrylic facade render primer with quartz sand.



PACKAGING

5kg/20kg



CONSUMPTION

0.25kg/m²

Description

NEOPRIM PRIMER GRAFIATO is a water-based, white, acrylic facade render primer with quartz sand. NEOPRIM PRIMER GRAFIATO ensures a uniformly coloured final surface, especially when a dark coloured render has been selected.

Area of Use

-It is used as a ready to use primer before applying the decorative render.

Substrate Preparation

The surface should be free of dust, grease, loose particles, paints, etc. It is recommended to dampen it before application.

Application

NEOPRIM PRIMER GRAFIATO should be thoroughly stirred before application, in slow, circular motions to prevent air entrapment. NEOPRIM PRIMER GRAFIATO is applied by brush or roller.

Consumption

It consumes 0.25kg/m² depending on the surface.

Features



Technical Data (IN +23° C AND 50% U.R.)

Appearance	Paste
Colour	White
Density (ISO2811, DIN 53217, ASTM D 1475)	1.65-1.75 g/cm ³
Viscosity (RVDV -2T,R7)	5500-6500 cp
Shear Stress (RVDV -2T,R7)	10000-15000 newton/m ²
Kinematic viscosity (RVDV -2T,R7)	2000-5000 mm ² /s
pH	≥8

NEON Paints

Tiranë, Albania

info@neonpaints.eu

www.neonpaints.eu

T: +355 69 20 94 570