

# PN-301 INTERIOR PRIMER

Premium emulsion, water-based primer with high adhesion and high penetration properties.



**PACKAGING**  
0.75L/3L/9L



**DRYING TIME**  
2-4 Hours



**CONSUMPTION**  
12-15 m<sup>2</sup>/L

## Description

PN-301 INTERIOR PRIMER is a normal emulsion, water-based primer with high adhesion and high penetration properties.

PN-301 INTERIOR PRIMER is ideal for use in indoor spaces as it is odourless, and environment- and user- friendly.

## Area of Use

-It is used for indoor applications, on new or old surfaces, on all common building materials, such as concrete, plaster, gypsum boards, etc.

## Substrate Preparation

The surface must be dry and free of dust, grease, dirt, etc.

## Application

PN-301 INTERIOR PRIMER is applied in one coat thinned up to 70% with clean water.

For highly porous substrates, use it undiluted. It is applied by brush, roller, or spray.

## Consumption

PN-301 INTERIOR PRIMER covers 12-15 m<sup>2</sup>/L depending on the surface.

## Features





## Technical Data (IN +23° C AND 50% U.R.)

Density	0.95-1.15 g/cm <sup>3</sup>
pH	7
Viscosity	1500-3000 mpa*s
Intermolecular Force	28000-55000 mpa
Drying Time	2-4 Hours

### NEON Paints

Tiranë, Albania

[info@neonpaints.eu](mailto:info@neonpaints.eu)

[www.neonpaints.eu](http://www.neonpaints.eu)

T: +355 69 20 94 570

THIS TECHNICAL DATA SHEET SUPERSEDES ALL PREVIOUS EDITIONS RELEVANT TO THIS PRODUCT

2/2

DISCLAIMER: The above technical data, information, recommendations and guidance are based on scientific and technical knowledge, laboratory studies and long experience. However, the above information is considered to be as indicative and should be reviewed in any case in relation to each specific application conditions. Consequently, the suitability of each product in any application must be evaluated after referring to the updated Technical Data Sheet and to the website [www.matis-eu.com](http://www.matis-eu.com), as well as after contacting the technical support department, in case of necessity. Our company guarantees the quality of the product itself, whilst in any case the user/applicant is exclusively responsible for any undesirable failures after using the product.