

# TOP WALL PAINT

Normal distemper paint formulated to offer breathability for the walls and ceilings with good coverage.



## PACKAGING

0.75L/3L/9L/15L



## DRYING TIME

2-3 Hours



## CONSUMPTION

3-4 m<sup>2</sup>/L

## Description

TOP WALL PAINT is a normal distemper paint formulated to offer breathability for the walls and ceilings with good coverage.

## Area of Use

-It is used for indoor applications, on new or old surfaces, on all common building materials, such as concrete, plaster, gypsum boards, etc.

## Substrate Preparation

The surface must be dry and free of dust, grease, dirt, etc. For surface smoothing, NEOSTUKO should be used. The surface must be primed with PN-101 PLASTIC PRIMER or PN-301 PLASTIC PRIMER to stabilize and increase the adhesion of the paint to the surface.

## Application

TOP WALL PAINT should be thoroughly stirred before use. It is applied as is or thinned with clean water, in two coats using a roller, brush, or airless gun. The second coat is applied once the first one has completely dried.

## Consumption

TOP WALL PAINT covers 3-4 m<sup>2</sup>/L depending on the surface.

## Features



## Technical Data (IN +23° C AND 50% U.R.)

Appearance	White emulsion
Density (ISO2811, DIN 53217, ASTM D 1475)	1.58-1.62 g/cm <sup>3</sup>
Viscosity (RVDV -2T,R7)	4000-6500 cp
Intermolecular forces (RVDV -2T,R7)	88000-125000 newton/m <sup>2</sup>
Kinematic viscosity (RVDV -2T,R7)	2400-4200 mm <sup>2</sup> /s
pH	≥8
Particle Size	10-40 μm

### NEON Paints

Tiranë, Albania

[info@neonpaints.eu](mailto:info@neonpaints.eu)

[www.neonpaints.eu](http://www.neonpaints.eu)

T: +355 69 20 94 570