

UNO ACRYLIC ULTRA WHITE

Premium quality acrylic paint formulated with “One Coat” technology with high water-repellence and resistance to weather conditions, aging and excellent coverage.



PACKAGING
3L/9L



DRYING TIME
2-3 Hours



CONSUMPTION
14-16 m²/L

Description

UNO ACRYLIC ULTRA WHITE is a premium quality acrylic paint formulated with “One Coat” technology with high water-repellence and resistance to weather conditions, aging and excellent coverage. UNO ACRYLIC ULTRA WHITE is vapour-permeable and has strong adhesion to any type of new or old substrates.

Area of Use

-It is used for exterior applications, on all common building materials, such as concrete, plaster, gypsum boards, etc.

Substrate Preparation

The surface must be dry and free of dust, grease, dirt, etc. For surface smoothing, NEOSTUKO should be used. The surface must be primed with AN-401 ACRYLIC PRIMER or AN-501 ACRYLIC PRIMER PINK to stabilize and increase the adhesion of the paint to the surface.

Application

UNO ACRYLIC ULTRA WHITE should be thoroughly stirred before use. It is applied as is or thinned with clean water, in two coats using a roller, brush, or airless gun. The second coat is applied once the first one has completely dried.

Consumption

UNO ACRYLIC ULTRA WHITE covers 14-16 m²/L depending on the surface.

Features



Technical Data (IN +23° C AND 50% U.R.)

Appearance	White emulsion
Density (ISO2811, DIN 53217, ASTM D 1475)	1.50-1.56 g/cm ³
Viscosity (RVDV -2T,R7)	5000-7000 cp
Intermolecular forces (RVDV -2T,R7)	80000-125000 newton/m ²
Kinematic viscosity (RVDV -2T,R7)	2500-5000 mm ² /s
pH	≥8
Particle Size	5-25 µm

NEON Paints

Tiranë, Albania

info@neonpaints.eu

www.neonpaints.eu

T: +355 69 20 94 570