

VELURA INTERIOR

Professional matt emulsion paint with good resistance to repeated washing and good coverage.



PACKAGING

0.75L/3L/9L



DRYING TIME

2-3 Hours



CONSUMPTION

8-10 m²/L

Description

VELURA INTERIOR is a professional matt emulsion paint with good resistance to repeated washing and good coverage. VELURA INTERIOR has good durability, for use on interior walls and ceilings. It has a good resistance to frequent washing and aging and provides strong adhesion to any type of new or old substrate.

Area of Use

-It is used for indoor applications, on new or old surfaces, on all common building materials, such as concrete, plaster, gypsum boards, etc.

Substrate Preparation

The surface must be dry and free of dust, grease, dirt, etc. For surface smoothing, NEOSTUKO should be used. The surface must be primed with PN-101 PLASTIC PRIMER or PN-301 PLASTIC PRIMER to stabilize and increase the adhesion of the paint to the surface.

Application

VELURA INTERIOR should be thoroughly stirred before use. It is applied as is or thinned with clean water, in two coats using a roller, brush, or airless gun. The second coat is applied once the first one has completely dried.

Consumption

VELURA INTERIOR covers 8-10 m²/L depending on the surface.

Features



Technical Data (IN +23° C AND 50% U.R.)

Appearance	White emulsion
Density (ISO2811, DIN 53217, ASTM D 1475)	1.56-1.60 g/cm ³
Viscosity (RVDV -2T,R7)	3500-5500 cp
Intermolecular forces (RVDV -2T,R7)	60000-120000 newton/m ²
Kinematic viscosity (RVDV -2T,R7)	2100-3500 mm ² /s
pH	≥8
Particle Size	10-40 μm

NEON Paints

Tiranë, Albania

info@neonpaints.eu

www.neonpaints.eu

T: +355 69 20 94 570