

CORROTEX PROFESSIONAL

Fast-dry, alkyd-based anti-rust primer with excellent adhesion.



PACKAGING
0.75L/3.75L



DRYING TIME
30 Min - 1 Hour



CONSUMPTION
10-12 m²/L

Description

CORROTEX PROFESSIONAL is a fast-dry, alkyd-based anti-rust primer with excellent adhesion. CORROTEX PROFESSIONAL provides protection to metal surfaces from rust.

Area of Use

-It is used for indoor and outdoor applications, on new or old metal surfaces, such as doors, tools, machinery, railings, handrails, etc.

Substrate Preparation

The surface must be dry and free of dust, grease, dirt, etc. Any imperfections should be rubbed with sandpaper.

Application

CORROTEX PROFESSIONAL should be thoroughly stirred before use. It is applied using a roller, brush, or airless spray gun. Apply two coats allowing the first coat to dry completely before applying the second. Drying time between two coats is 30 minutes – 1 hour depending on the atmospheric conditions.

Consumption

CORROTEX PROFESSIONAL covers 10-12 m²/L depending on the surface.

Features





Technical Data (IN +23 °C AND 50% U.R.)

Form	Liquid
Colour	See Catalog
Storage	12 months if stored in original sealed packaging in a dry place
Fineness	5 – 40 µm
Viscosity Deep Cup 4	200 – 300 sec
Density	0.94 – 1.35 g/ml
Coverage	10 – 12 m ² /L
Drying Time	30 Min - 1 Hour
Dangerous Substances	See SDS

NEON Paints

Tiranë, Albania

info@neonpaints.eu

www.neonpaints.eu

T: +355 69 20 94 570

THIS TECHNICAL DATA SHEET SUPERSEDES ALL PREVIOUS EDITIONS RELEVANT TO THIS PRODUCT

2/2

DISCLAIMER: The above technical data, information, recommendations and guidance are based on scientific and technical knowledge, laboratory studies and long experience. However, the above information is considered to be as indicative and should be reviewed in any case in relation to each specific application conditions. Consequently, the suitability of each product in any application must be evaluated after referring to the updated Technical Data Sheet and to the website www.matis-eu.com, as well as after contacting the technical support department, in case of necessity. Our company guarantees the quality of the product itself, whilst in any case the user/applicant is exclusively responsible for any undesirable failures after using the product.