

FERROX PROFESSIONAL

Fast-dry, alkyd-based paint with high quality finish and excellent durability.



PACKAGING

0.75L/3.75L



DRYING TIME

30 Min - 1 Hour



CONSUMPTION

14-16 m²/L

Description

FERROX PROFESSIONAL is a fast-dry, alkyd-based paint with high quality finish and excellent durability. FERROX PROFESSIONAL provides high hardness, resistance to weather conditions and aging.

Area of Use

-It is used for indoor and outdoor applications, on new or old metal surfaces, such as doors, tools, machinery, railings, handrails, etc.

Substrate Preparation

The surface must be dry and free of dust, grease, dirt, etc. The surface must be primed with CORRO-TEX PROFESSIONAL.

Application

FERROX PROFESSIONAL should be thoroughly stirred before use. It is applied using a roller, brush, or airless spray gun. Apply two coats allowing the first coat to dry completely before applying the second. Drying time between two coats is 30 minutes – 1 hour depending on the atmospheric conditions.

Consumption

FERROX PROFESSIONAL covers 14-16 m²/L depending on the surface.

Features



Technical Data (IN +23° C AND 50% U.R.)

Form	Liquid
Colour	See Catalog
Storage	12 months if stored in original sealed packaging in a dry place
Fineness	5 – 40 µm
Viscosity Deep Cup 4	200 – 300 sec
Density	0.94 – 1.35 g/ml
Coverage	10 – 12 m ² /L
Drying Time	30 Min - 1 Hour
Dangerous Substances	See SDS

NEON Paints

Tiranë, Albania

info@neonpaints.eu

www.neonpaints.eu

T: +355 69 20 94 570