

# ORALAC PROFESSIONAL

Alkyd-based paint with high quality finish and excellent durability.



**PACKAGING**  
0.75L/3.75L



**DRYING TIME**  
4-6 Hours



**CONSUMPTION**  
14-16 m<sup>2</sup>/L

## Description

ORALAC PROFESSIONAL is an alkyd-based paint with high quality finish and excellent durability. ORALAC PROFESSIONAL provides high hardness, resistance to weather conditions and aging.

## Area of Use

-It is used for indoor and outdoor applications, on new or old metal surfaces, such as doors, tools, machinery, railings, handrails, etc.

## Substrate Preparation

The surface must be dry and free of dust, grease, dirt, etc. The surface must be primed with ANTIRUST PROFESSIONAL or ANTICOR PROFESSIONAL.

## Application

ORALAC PROFESSIONAL should be thoroughly stirred before use. It is applied using a roller, brush, or airless spray gun. For brush or roller application, thin up to 5% with NW-13.00 SPINITRO, and for airless spray application thin 10-20% with NX-20.00 SOLVETON.

Apply two coats allowing the first coat to dry completely before applying the second.

## Consumption

ORALAC PROFESSIONAL covers 14-16 m<sup>2</sup>/L depending on the surface.

## Features



 **NEON COLORING SYSTEM**  
**BASES**  
A - B - C



## Technical Data (IN +23 °C AND 50% U.R.)

Form	Liquid
Colour	See Catalog
Storage	12 months if stored in original sealed packaging in a dry place
Fineness	5 – 40 µm
Viscosity Deep Cup 4	200 – 300 sec
Density	0.94 – 1.35 g/ml
Coverage	10 – 12 m2/L
Drying Time	4-6 Hours
Dangerous Substances	See SDS

### NEON Paints

Tiranë, Albania

info@neonpaints.eu

www.neonpaints.eu

T: +355 69 20 94 570

THIS TECHNICAL DATA SHEET SUPERSEDES ALL PREVIOUS EDITIONS RELEVANT TO THIS PRODUCT

2/2

DISCLAIMER: The above technical data, information, recommendations and guidance are based on scientific and technical knowledge, laboratory studies and long experience. However, the above information is considered to be as indicative and should be reviewed in any case in relation to each specific application conditions. Consequently, the suitability of each product in any application must be evaluated after referring to the updated Technical Data Sheet and to the website [www.matis-eu.com](http://www.matis-eu.com), as well as after contacting the technical support department, in case of necessity. Our company guarantees the quality of the product itself, whilst in any case the user/applicant is exclusively responsible for any undesirable failures after using the product.