

ELITE ECO INTERIOR

Ecological matt emulsion paint with high resistance to repeated washing and high coverage.



PACKAGING
0.75L/3L/9L



DRYING TIME
2-3 Hours



CONSUMPTION
13-15 m²/L per one coat

Description

ELITE ECO INTERIOR is an ecological matt emulsion paint with high resistance to repeated washing and high coverage. ELITE ECO INTERIOR has good durability, for use on interior walls and ceilings. It has a good resistance to frequent washing and aging and provides strong adhesion to any type of new or old substrate.

Area of Use

-It is used for indoor applications, on new or old surfaces, on all common building materials, such as concrete, plaster, gypsum boards, etc.

Substrate Preparation

The surface must be dry and free of dust, grease, dirt, etc. For surface smoothing, NEOSTUKO should be used. The surface must be primed with PN-101 PLASTIC PRIMER or PN-301 PLASTIC PRIMER to stabilize and increase the adhesion of the paint to the surface.

Application

ELITE ECO INTERIOR should be thoroughly stirred before use. It is applied as is or thinned with clean water, in two coats using a roller, brush, or airless gun. The second coat is applied once the first one has completely dried.

Consumption

ELITE ECO INTERIOR covers 13-15 m²/L per one coat depending on the surface.

Storage

Recommended storage temperature: 5 °C–38 °C. Containers should remain sealed and stored in a cool, dry environment.

Features



**NEON
COLORING
SYSTEM**

**BASES
A - B**

Technical Data (IN +23° C AND 50% U.R.)

Appearance	White emulsion
Density (ISO2811, DIN 53217, ASTM D 1475)	1.56-1.60 g/cm ³
Viscosity (RVDV -2T,R7)	3500-7500 cp
Intermolecular forces (RVDV -2T,R7)	85000-140000 newton/m ²
Kinematic viscosity (RVDV -2T,R7)	2100-4500 mm ² /s
pH	≥8
Particle Size	10-30 µm

NEON Paints

Tiranë, Albania

info@neonpaints.eu

www.neonpaints.eu

T: +355 69 20 94 570