

UNO WALL PAINT

Premium quality distemper paint formulated to offer breathability for the walls and ceilings with great coverage.



PACKAGING
0.75L/3L/9L



DRYING TIME
2-3 Hours



CONSUMPTION
13-15 m²/L per one coat

Description

UNO WALL PAINT is a premium quality distemper paint formulated to offer breathability for the walls and ceilings with great coverage.

Area of Use

-It is used for indoor applications, on new or old surfaces, on all common building materials, such as concrete, plaster, gypsum boards, etc.

Substrate Preparation

The surface must be dry and free of dust, grease, dirt, etc. For surface smoothing, NEOSTUKO should be used. The surface must be primed with PN-101 PLASTIC PRIMER or PN-301 PLASTIC PRIMER to stabilize and increase the adhesion of the paint to the surface.

Application

UNO WALL PAINT should be thoroughly stirred before use. It is applied as is or thinned with clean water, in two coats using a roller, brush, or airless gun. The second coat is applied once the first one has completely dried.

Consumption

UNO WALL PAINT covers 13-15 m²/L per one coat depending on the surface.

Storage

Recommended storage temperature: 5 °C–38 °C. Containers should remain sealed and stored in a cool, dry environment.

Features



NEON
COLORING
SYSTEM

BASES
A

Technical Data (IN +23° C AND 50% U.R.)

Appearance	White emulsion
Density (ISO2811, DIN 53217, ASTM D 1475)	1.55-1.59 g/cm ³
Viscosity (RVDV -2T,R7)	4000-6700 cp
Intermolecular forces (RVDV -2T,R7)	85000-120000 newton/m ²
Kinematic viscosity (RVDV -2T,R7)	2500-4300 mm ² /s
pH	≥8
Particle Size	5-25 µm

NEON Paints

Tiranë, Albania

info@neonpaints.eu

www.neonpaints.eu

T: +355 69 20 94 570