

PN-101 INTERIOR PRIMER

Normal emulsion, water-based primer with good adhesion and good penetration properties.



PACKAGING

0.75L/3L/9L



DRYING TIME

2-4 Hours



CONSUMPTION

3-5 m²/L per one coat

Description

PN-101 INTERIOR PRIMER is a normal emulsion, water-based primer with good adhesion and good penetration properties.

PN-101 INTERIOR PRIMER is ideal for use in indoor spaces as it is odourless, and environment- and user- friendly.

Area of Use

-It is used for indoor applications, on new or old surfaces, on all common building materials, such as concrete, plaster, gypsum boards, etc.

Substrate Preparation

The surface must be dry and free of dust, grease, dirt, etc.

Application

PN-101 INTERIOR PRIMER is applied in one coat thinned up to 50% with clean water.

For highly porous substrates, use it undiluted. It is applied by brush, roller, or spray. Suitable for application in conditions ranging from 5 °C to 35 °C and at relative humidity below 80%.

Consumption

PN-101 INTERIOR PRIMER covers 3-5 m²/L per one coat depending on the surface.

Storage

Recommended storage temperature: 5 °C–38 °C. Containers should remain sealed and stored in a cool, dry environment.

Features





Technical Data (IN +23 °C AND 50% U.R.)

Density	0.9-1.1 g/cm ³
pH	7
Viscosity	1000-2000 mpa*s
Intermolecular Force	27790-42000 mpa
Drying Time	2-4 Hours

NEON Paints

Tiranë, Albania

info@neonpaints.eu

www.neonpaints.eu

T: +355 69 20 94 570

THIS TECHNICAL DATA SHEET SUPERSEDES ALL PREVIOUS EDITIONS RELEVANT TO THIS PRODUCT

2/2

DISCLAIMER: The above technical data, information, recommendations and guidance are based on scientific and technical knowledge, laboratory studies and long experience. However, the above information is considered to be as indicative and should be reviewed in any case in relation to each specific application conditions. Consequently, the suitability of each product in any application must be evaluated after referring to the updated Technical Data Sheet and to the website www.matis-eu.com, as well as after contacting the technical support department, in case of necessity. Our company guarantees the quality of the product itself, whilst in any case the user/applicant is exclusively responsible for any undesirable failures after using the product.