

NEOLAC AQUA SATIN

Premium water-based satin paint for wooden surfaces.



PACKAGING
0.75L/3.75L



DRYING TIME
30 Min - 1 Hour



CONSUMPTION
10-12 m²/L per one coat

Description

NEOLAC AQUA SATIN is a premium water-based satin paint for wooden surfaces. It offers high flexibility, excellent coverage, and strong resistance to frequent washing and weather conditions. It provides strong adhesion and excellent workability.

Area of Use

Suitable for interior and exterior applications on new or old wood, metal, plaster, galvanized surfaces, etc.

Substrate Preparation

The surface must be dry and free from dust, grease, dirt, and other contaminants. Any irregularities should be sanded with sandpaper. The surface should be treated with NEOLAC AQUA PRIMER (for wooden or plaster surfaces) or ANTI-RUST PROFESSIONAL (for metal surfaces).

Application

NEOLAC AQUA SATIN should be stirred well before use. It can be applied with a roller, brush, or airless spray gun. For brush or roller application, dilute with 5–10% water. For airless spray application, dilute with 10–20% water. Apply two coats, allowing the first coat to dry completely before applying the second coat.


Consumption

It covers 10-12 m²/L per one coat depending on the surface.

Storage

Recommended storage temperature: 5 °C–38 °C. Containers should remain sealed and stored in a cool, dry environment.

Features



Technical Data (IN +23 °C AND 50% U.R.)

Form	Water-based enamel paint
Colours	White and other colours on request
Volume solids	42 ± 2 %
Density	1.32 kg/l
Viscosity (Poise)	15-20
pH	8-9 at +23°C
Capillary water absorption	0.05 kg/m ² h ^{0.5}
Bond strength	2.0 N/mm ²
Gloss level	15-45 at 60°
Whiteness	≥ 95%
Drying time	30-60 min (touch dry)
Recoat time	4-6 h

NEON Paints

Tiranë, Albania

info@neonpaints.eu

www.neonpaints.eu

T: +355 69 20 94 570

THIS TECHNICAL DATA SHEET SUPERSEDES ALL PREVIOUS EDITIONS RELEVANT TO THIS PRODUCT

2/2

DISCLAIMER: The above technical data, information, recommendations and guidance are based on scientific and technical knowledge, laboratory studies and long experience. However, the above information is considered to be as indicative and should be reviewed in any case in relation to each specific application conditions. Consequently, the suitability of each product in any application must be evaluated after referring to the updated Technical Data Sheet and to the website www.matis-eu.com, as well as after contacting the technical support department, in case of necessity. Our company guarantees the quality of the product itself, whilst in any case the user/applicant is exclusively responsible for any undesirable failures after using the product.