

NEOLAC NEOPROTECT

Premium clear wood preservative and protective impregnation.



PACKAGING

0.75L/3.75L



DRYING TIME

12 Hours



CONSUMPTION

12-15 m²/L per one coat

Description

NEOLAC NEOPROTECT is a premium clear wood preservative and protective impregnation. It penetrates deep into the wood and protects it from woodworm, fungi and blue stains.

Area of Use

-It is suitable for all exterior woodwork, e.g. doors, windows, wooden constructions, garden furniture, etc., to protect from woodworm, fungi, blue stain, or decay while bringing out the natural beauty of the wood piece.

Substrate Preparation

The surface should be dry and free of dust, oil, grease, loose particles, etc., while any imperfections should be smoothed down with sandpaper.

Application

Stir NEOLAC NEOPROTECT well before use. Apply undiluted with a brush, roller or airless gun in two or three coats. Apply each coat when the previous one is fully dried.

Consumption

It covers 12-15 m²/L per one coat depending on the surface.

Storage

Recommended storage temperature: 5 °C–38 °C. Containers should remain sealed and stored in a cool, dry environment.

Features





Technical Data (IN +23° C AND 50% U.R.)

Density (EN ISO 2811- 1)	0.79-0.83 kg/l
Viscosity (EN ISO 2884- 2)	15 (23°C)
Drying Time (EN ISO 9117)	12 h
Recoat Time (EN ISO 9117)	24 h
Dangerous Substances	Check SDS

NEON Paints

Tiranë, Albania

info@neonpaints.eu

www.neonpaints.eu

T: +355 69 20 94 570

THIS TECHNICAL DATA SHEET SUPERSEDES ALL PREVIOUS EDITIONS RELEVANT TO THIS PRODUCT

2/2

DISCLAIMER: The above technical data, information, recommendations and guidance are based on scientific and technical knowledge, laboratory studies and long experience. However, the above information is considered to be as indicative and should be reviewed in any case in relation to each specific application conditions. Consequently, the suitability of each product in any application must be evaluated after referring to the updated Technical Data Sheet and to the website www.matis-eu.com, as well as after contacting the technical support department, in case of necessity. Our company guarantees the quality of the product itself, whilst in any case the user/applicant is exclusively responsible for any undesirable failures after using the product.