

NEOLAC STONE

Premium, transparent, alkyd-based protective stone varnish.



PACKAGING

0.75L/3.75L



DRYING TIME

1-2 Hours



CONSUMPTION

10-12 m²/L per one coat

Description

NEOLAC STONE is a premium, transparent, alkyd-based protective stone varnish. It provides high water repellence, durable long-lasting protection, UV-stable and it enhances the natural colour of the material.

Area of Use

-It enhances the natural beauty of the surface whilst protecting it from rain, weather conditions and air pollution. Its highly effective impregnating formula is suitable for natural stone, exposed masonry, roof tiles, etc. For interior and exterior use on wall and floor surfaces.

Substrate Preparation

The surface should be dry and free of dust, oil, grease, loose particles, etc. The surface should have open pores to be treated with NEOLAC STONE.

Application

Stir NEOLAC STONE well before use. Apply with a brush, roller or airless gun in two coats. Apply each coat when the previous one is fully dried.

Consumption

It covers 10-12 m²/L per one coat depending on the surface.

Storage

Recommended storage temperature: 5 °C–38 °C. Containers should remain sealed and stored in a cool, dry environment.

Features



Technical Data (IN +23° C AND 50% U.R.)

Density: (EN ISO 2811- 1)	0.92 ± 0.02 kg/l
Viscosity (mPa.s): (EN ISO 2884- 2)	560 (23°C)
Capillary water absorption: (EN ISO 1062- 3: W3 Low, w ≤ 0,1)	0.02 kg/m ² /h0.5
Adhesion: (EN ISO 4624)	2 N/mm ²
Drying time: (EN ISO 9117)	1-2 h (touch dry)
Recoat time: (EN ISO 9117)	3-4 h
Dangerous Substances	Check SDS

NEON Paints

Tiranë, Albania

info@neonpaints.eu

www.neonpaints.eu

T: +355 69 20 94 570

THIS TECHNICAL DATA SHEET SUPERSEDES ALL PREVIOUS EDITIONS RELEVANT TO THIS PRODUCT

2/2

DISCLAIMER: The above technical data, information, recommendations and guidance are based on scientific and technical knowledge, laboratory studies and long experience. However, the above information is considered to be as indicative and should be reviewed in any case in relation to each specific application conditions. Consequently, the suitability of each product in any application must be evaluated after referring to the updated Technical Data Sheet and to the website www.matis-eu.com, as well as after contacting the technical support department, in case of necessity. Our company guarantees the quality of the product itself, whilst in any case the user/applicant is exclusively responsible for any undesirable failures after using the product.