

# NEOLAC WOOD

Premium, alkyd-based wood varnish for woodwork.



## PACKAGING

0.75L/3.75L



## DRYING TIME

4-6 Hours



## CONSUMPTION

14-16 m<sup>2</sup>/L per one coat

## Description

NEOLAC WOOD is a premium, alkyd-based wood varnish for woodwork. It is highly durable to weather conditions and aging.

## Area of Use

-It is used for for all exterior and interior woodwork, e.g. doors, windows, wooden constructions, garden furniture, etc., to protect and bring out the natural beauty of wood.

## Substrate Preparation

The surface should be dry and free of dust, oil, grease, loose particles, etc., while any imperfections should be smoothed down with sandpaper. It is recommended to apply two coats of NEOLAC NEOPROTECT to protect the surface from fungi and woodworms.

## Application

Stir NEOLAC WOOD well before use. For brush or roller application, thin up to 5% with thinner. The second coat is applied as soon as the first one has completely dried.

## Consumption

It covers 14-16 m<sup>2</sup>/L per one coat depending on the surface.

## Storage

Recommended storage temperature: 5 °C–38 °C. Containers should remain sealed and stored in a cool, dry environment.

## Features



## Technical Data (IN +23° C AND 50% U.R.)

Density: (EN ISO 2811- 1)	0.92 ± 0.02 kg/l
Viscosity (mPa.s): (EN ISO 2884- 2)	560 (23°C)
Capillary water absorption: (EN ISO 1062- 3: W3 Low, w ≤ 0,1)	0.02 kg/m <sup>2</sup> /h0.5
Adhesion: (EN ISO 4624)	2 N/mm <sup>2</sup>
Drying time: (EN ISO 9117)	4-6 h (touch dry)
Recoat time: (EN ISO 9117)	3-4 h
Dangerous Substances	Check SDS

### NEON Paints

Tiranë, Albania

[info@neonpaints.eu](mailto:info@neonpaints.eu)

[www.neonpaints.eu](http://www.neonpaints.eu)

T: +355 69 20 94 570

THIS TECHNICAL DATA SHEET SUPERSEDES ALL PREVIOUS EDITIONS RELEVANT TO THIS PRODUCT

2/2

DISCLAIMER: The above technical data, information, recommendations and guidance are based on scientific and technical knowledge, laboratory studies and long experience. However, the above information is considered to be as indicative and should be reviewed in any case in relation to each specific application conditions. Consequently, the suitability of each product in any application must be evaluated after referring to the updated Technical Data Sheet and to the website [www.matis-eu.com](http://www.matis-eu.com), as well as after contacting the technical support department, in case of necessity. Our company guarantees the quality of the product itself, whilst in any case the user/applicant is exclusively responsible for any undesirable failures after using the product.