

Premium, water-based undercoat primer for woodwork.



PACKAGING
0.75L/3.75L



DRYING TIME
1-2 Hours



CONSUMPTION
10-12 m²/L per one coat

Description

NEOSTAR AQUA is a premium, water-based undercoat primer for woodwork. It offers excellent adhesion to the substrate and great coverage.

Area of Use

-It is used for indoor or outdoor applications, on new or old wood surfaces.

Substrate Preparation

The surface should be dry and free of dust, oil, grease, loose particles, etc., while any imperfections should be smoothed down with sandpaper. The surface should be primed with NEOSTAR AQUA.

Application

Stir NEOLAC AQUA well before use. For brush or roller application, thin up to 5-10% with clean water, and for airless spray application thin 20-30%. After drying, it should be rubbed down with sandpaper to form a smooth surface for the paint coat. Suitable for application in conditions ranging from 5°C to 35°C and at relative humidity below 80%.


Consumption

It covers 10-12m²/L per one coat depending on the surface.

Storage

Recommended storage temperature: 5°C–38°C. Containers should remain sealed and stored in a cool, dry environment.

Features





Technical Data (IN +23° C AND 50% U.R.)

Density	1.25 kg
pH	8-9 (23°C)
Bonding Strength	2.0 N/mm ²
Capillary water absorption	0.05 kg/m ² h 0.5
Viscosity	15-20
Drying Time	1 Hours
Recoat Time	4-6 Hours

NEON Paints

Tiranë, Albania

info@neonpaints.eu

www.neonpaints.eu

T: +355 69 20 94 570

THIS TECHNICAL DATA SHEET SUPERSEDES ALL PREVIOUS EDITIONS RELEVANT TO THIS PRODUCT

DISCLAIMER: The above technical data, information, recommendations and guidance are based on scientific and technical knowledge, laboratory studies and long experience. However, the above information is considered to be as indicative and should be reviewed in any case in relation to each specific application conditions. Consequently, the suitability of each product in any application must be evaluated after referring to the updated Technical Data Sheet and to the website www.matis-eu.com, as well as after contacting the technical support department, in case of necessity. Our company guarantees the quality of the product itself, whilst in any case the user/applicant is exclusively responsible for any undesirable failures after using the product.