

RS 35 ROOF STOP

Acrylic-based, ready-to-use, elastomeric liquid membrane for waterproofing.



PACKAGING
0.75L/3L/9L



CONSUMPTION
5 m²/L per one coat

Description

RS 35 ROOF STOP is an acrylic-based, ready-to-use, elastomeric liquid membrane for waterproofing. It is highly flexible, and vapor permeable for waterproofing of wet areas.

Area of Use

It is ideal for seamless and jointless waterproofing of surfaces in wet areas, such as bathrooms, showers, etc., prior to tile installation. It is suitable for all floor or wall surfaces made of concrete, plaster, gypsum boards, chipboards, etc. Not suitable for surfaces subject to permanent water pressure.

Substrate Preparation

The surface should be dry and free of dust, oil, grease, loose particles, etc. The surface should be primed with AN-401 ACRYLIC PRIMER.

Application

After the primer has dried, RS 35 ROOFS STOP is applied with a brush or roller in two layers, diluted with water up to 4% by weight if necessary. The second layer should be applied after the first one has dried.

Consumption

GLORIA BETACRYL covers 5 m²/L per one coat depending on the surface.

Storage

Recommended storage temperature: 5°C–38°C. Containers should remain sealed and stored in a cool, dry environment.

Features



Technical Data (IN +23 °C AND 50% U.R.)

Form	Liquid
Color	White/Grey
Storage	24 months when stored in the original sealed packaging in a dry place.
Consumption	2-2.5kg/m ²
Application Temperature	(+5 °C) - (+35 °C)
Maximal thickness for two layers	0.75-1 mm
Tensile Strength (EN 1542)	≥0.8 N/mm ²
Tensile Adhesion Strength After Heat Ageing (EN 1062-11/EN 1542)	≥0.8 N/mm ²
Capillary Water Absorbion (EN ISO 1063-3)	<0.1kg/m ² h0.5
Crack Bridging (EN 1062-7)(21 °C)	≥2.5mm (A5)/ ≥1.5mm (A4)
Reaction to fire	Cs1d0
Dangerous Substances	See SDS

NEON Paints

Tiranë, Albania

info@neonpaints.euwww.neonpaints.eu

T: +355 69 20 94 570