

# ZN-701 BITUMINOUS EMULSION

Bituminous waterproofing emulsion for bonding bituminous sheet membranes.



## PACKAGING

3L/9L



## CONSUMPTION

3-4 m<sup>2</sup>/L per one coat

### Description

ZN-701 BITUMINOUS EMULSION is a bituminous waterproofing emulsion for bonding bituminous sheet membranes.

### Area of Use

It is used for waterproofing of concrete surfaces, such as flat roofs, foundations, external walls, floors. It is used as a primer prior to bonding bituminous waterproofing membranes and for maintenance of existing bituminous layers.

### Substrate Preparation

The surface should be dry and free of dust, oil, grease, loose particles, etc.

### Application

ZN-701 BITUMINOUS EMULSION should be stirred well before application. It is applied by brush or roller. ZN-701 BITUMINOUS EMULSION is applied as a primer by diluting it with 50% water the first layer and it is necessary to use two other layers that are diluted with 25% after the first layer is dried.

### Consumption

It covers 3-4m<sup>2</sup>/L depending on the surface.

### Storage

Recommended storage temperature: 5°C–38°C. Containers should remain sealed and stored in a cool, dry environment.

### Features



## Technical Data (IN +23 °C AND 50% U.R.)

Form	Liquid
Color	Black
Storage	24 months when stored in the original sealed packaging in a dry place.
Consumption	1.5-2.5k/m <sup>2</sup>
Application Temperature	(+5°C) - (+35°C)
Density	1g/cm <sup>3</sup>
Solid material ratio	48%

### NEON Paints

Tiranë, Albania

[info@neonpaints.eu](mailto:info@neonpaints.eu)

[www.neonpaints.eu](http://www.neonpaints.eu)

T: +355 69 20 94 570

THIS TECHNICAL DATA SHEET SUPERSEDES ALL PREVIOUS EDITIONS RELEVANT TO THIS PRODUCT

2/2

DISCLAIMER: The above technical data, information, recommendations and guidance are based on scientific and technical knowledge, laboratory studies and long experience. However, the above information is considered to be as indicative and should be reviewed in any case in relation to each specific application conditions. Consequently, the suitability of each product in any application must be evaluated after referring to the updated Technical Data Sheet and to the website [www.matis-eu.com](http://www.matis-eu.com), as well as after contacting the technical support department, in case of necessity. Our company guarantees the quality of the product itself, whilst in any case the user/applicant is exclusively responsible for any undesirable failures after using the product.